

EXPERIENCE

WORK X

- 新办公体验 -

POLYPROPYLENE
SERIES

MODULAR CARPET

Commercial Modular Carpet By Office

Commercial Modular Carpet
By Office

Our products can be installed
in numerous patterns,
giving you endless design
possibilities.

MODULAR CARPET



Quarter Turn


COLOR
71012321



狮子座 COLORS



71012311



71012312



71012313



71012321



71012341



71012331

SPECIFICATION

Construction: Multi-Level Loop
 Pile Fiber Composition: 100% Polypropylene
 Tufting Gauge: 1/12"
 Dye Method: Solution Dyed
 Pile Weight: 480g/m²
 Pile Height: 3mm/4mm/5mm
 Total Thickness: Approx 6.0mm
 Primary Backing: Polyester Spunbonded
 Backing Structure: Glass Reinforced PVC
 Tile Size: 500mm × 500mm



Quarter Turn

COLOR
71012311




Quarter Turn

COLOR
71112312



处女座 COLORS



71112311



71112312



71112321



71112322



71112331



71112323

SPECIFICATION

Construction: Multi-Level Loop
 Pile Fiber Composition: 100% Polypropylene
 Tufting Gauge: 1/12"
 Dye Method: Solution Dyed
 Pile Weight: 480g/m²
 Pile Height: 3mm/4mm/5mm
 Total Thickness: Approx 6.0mm
 Primary Backing: Polyester Spunbonded
 Backing Structure: Glass Reinforced PVC
 Tile Size: 500mm × 500mm



Quarter Turn

COLOR
71112323



Quarter Turn

COLOR

71212321



Quarter Turn

COLOR

71212312



双子座 COLORS



71212311



71212312



71212321



71212331

SPECIFICATION

Construction: Multi-Level Loop
 Pile Fiber Composition: 100% Polypropylene
 Tufting Gauge: 1/12"
 Dye Method: Solution Dyed
 Pile Weight: 480g/m²
 Pile Height: 3mm/4mm/5mm
 Total Thickness: Approx 6.0mm
 Primary Backing: Polyester Spunbonded
 Backing Structure: Glass Reinforced PVC
 Tile Size: 500mm × 500mm


RECOMMENDED INSTALLATION METHODS




Quarter Turn




Monolithic



Ashlar



Brick



Random

Anti-Bacteria:	Pass AATCC 174 Anti-bacteria Test	Pass AATCC 174 Anti-bacteria Test	Pass AATCC 174 Anti-bacteria Test
Anti-soiling:	Pass AATCC 175 Stain Resistance	Pass AATCC 175 Stain Resistance	Pass AATCC 175 Stain Resistance
TVOC:	GB18587-2001 ≤ 0.500 mg/m ³ h A	GB18587-2001 ≤ 0.500 mg/m ³ h A	GB18587-2001 ≤ 0.500 mg/m ³ h A
Formaldehyde:	GB18587-2001 ≤ 0.050 mg/m ³ h A	GB18587-2001 ≤ 0.050 mg/m ³ h A	GB18587-2001 ≤ 0.050 mg/m ³ h A
Styrene:	GB18587-2001 ≤ 0.400 mg/m ³ h A	GB18587-2001 ≤ 0.400 mg/m ³ h A	GB18587-2001 ≤ 0.400 mg/m ³ h A
4-Phenylcyclohexene:	GB18587-2001 ≤ 0.050 mg/m ³ h A	GB18587-2001 ≤ 0.050 mg/m ³ h A	GB18587-2001 ≤ 0.050 mg/m ³ h A



Quarter Turn 71212311

COLOR

FOUR CHARACTERISTICS OF THE PRODUCT

EXTREME SPEED PAVING, CREATIVITY

On the day of paving, you can take care of it and change it easily. Many colors can be paved according to the industry.

ENVIRONMENTAL PROTECTION

By ENVIROSTRAND becoming PET carpet fiber, less energy is required for manufacturing, a patented process is used to enhance yarn strength, and a multi-step purification process is used to ensure that the carpet resists dirt, dirt and contaminants.

EnviroStrand Fiber also offers a flexible set of color options for producing new product styles.

EnviroStrand solution dyed fiber's industry leadership in sustainability and design complements the creation of reliable, high performance, visually stunning carpets.

IMPROVE COMFORT UNDER THE FEET

Modular carpet - improves the comfort of your feet and effectively alleviates the cumulative benefits of employee fatigue in the office for a few months.

It will have a major impact on overall health, while a good office environment can improve work efficiency and improve morale!

Comfort is also an important part of the overall customer experience, creating a more relaxed and enjoyable environment for customers~

Comfort plus cushion support provides improved ergonomics, especially for sitting upright workstations, reducing leg muscle fatigue by up to 24%

ACOUSTIC NOISE REDUCTION FOR IMPROVED WORK EFFICIENCY

Tested with good iic performance, the impact insulation grade can greatly reduce the noise.

According to research, open office design increases teamwork communication and productivity while increasing workplace noise in the interactive space. Employees waste 759 hours a year. One-third of employees work up to three hours a day, up to 60 hours a month, or 759 hours a year. According to the 2013 Global Workplace Report, the Gallup office was interrupted every 11 minutes (on average). When interrupted, we need up to 23 minutes to get the brain back to the task at hand. According to the US Environmental Protection Agency (EPA), noise causes increased anxiety, decreased productivity, and increased personal stress, especially in the work environment. Reducing noise levels has a significant impact on building occupants.

Scientific office acoustic noise reduction:

- Increased ability to focus on work tasks by 48%;
- Reduce interference by 51%;
- Reduce error rate - 10% increase in accuracy and short-term memory;
- Reduce stress - physical symptoms of stress are reduced by 27%;



EXTREME SPEED PAVING
CREATIVITY




ENVIRONMENTAL PROTECTION



IMPROVE COMFORT
UNDER THE FEET



ACOUSTIC NOISE REDUCTION FOR IMPROVED
WORK EFFICIENCY



Random

COLOR
71012311
71012321

INSPECTION BEFORE INSTALLATION

- Do not begin installation if the subfloor temperature is below 10°C.
- The installation area 's ambient relative humidity must not exceed 65%.
- The substrates must be structurally sound, clean, level and dry.
- The substrate must be free of dust, dirt, loose particles and any other substance.

MODULAR CARPET

Commercial modular carpet products have Stain Release property by fluoridation. Because of its antifouling effect, stains are not easily stuck to the surface and a good appearance can last.

It also shows an excellent water & oil repellent performance. Even if water or oil is spilt, the surface of the carpets will repel them. Once you wipe them off, the stain cannot be left.